

Length	6040mm	
Width	2480mm	
Height	3210mm	High-floor standard cab(without air spoiler)
	3540mm	High-floor standard cab(with air spoiler)
	3745mm	High-floor high-roof cab(without air spoiler)
	3850mm	High-floor high-roof cab(with air spoiler)
Front overhang/rear	1540/1000mm	
Track	Track front	2022mm
	Track rear	1830mm
Cab	Brand-new A7cab,4-point full-floating air suspension,adjustable steering wheel with various heights and angles,air suspension seat,central door lock,electric window lifter,power mirror	
Engine	Sinotruk's new D12 series;turbocharged with inter-cooling;high-pressure common-rail fuel injecting system with maximum pressure of 1600bar;national IIIemissin standard;power range;340-460hp; D10 series engine as option	
Clutch	Sinotruk's 430 diaphragm sping clutch	
Gear box	Sinotruk's HW20716A gearbox,SmartShift automated mechanical transmission	
Front axle	New HW07 single reduction driving axle;ST16 double reduction driving axle as option	
Rear axle	HW single reduction drive axle;ST16 double reduction drive axle as option	
Tire	315/80R22.5 tubeless tire	
Brake system	Front disc rear shoes brake, four-circuit protection valve,EVB brake actuator, ABS+ASR+EBL+TPM	
Frame	High-strength single U-profile frame with a section of 300×90×8	
Electrical system	24V. CAN bus intellectual electronic control system	